

# H.264 Multiplex Real Time Network DVR

Support 3G ~ 3.5G Mobile Phone / PDA / I Phone / BlackBerry

MODEL 2-DVR4N-09, 2-DVR8N-06  
& 2-DVR16N11



## High Resolution H.264 Multiplex 4CH / 8CH / 16CH Network DVR with Smart GUI Interface



- ▶ H.264 Baseline: 4 recording video quality levels or user defined
- ▶ Multiplex 4/8/16 CH H.264 DVR: live, recording, playback, back up, network access and control
- ▶ NTSC / PAL software switch and channel Privacy Mask
- ▶ Support one HDD up to 2000GB, USB Backup with Media Player Format
- ▶ Audio 4CH In / 1CH Out (4CH) or 8CH In / 1 CH Out (8CH) or Audio 16CH In / 16CH Out (16CH)
- ▶ Network capability with Static IP, PPPoE, DHCP and DDNS
- ▶ Remote live view, backup, playback, PTZ control menu setup
- ▶ Dual streaming adjusted for limited upload bandwidth 3GPP support
- ▶ Up to 5 users account with different authority assigned
- ▶ Multi-lingual support, Client player (CMS) and AVI conversion Utility



Highest Quality – Best Performance

## 2-DVR4N-09, 2-DVR8N-06 & 2-DVR16N-11

Specification	4 Channel	8 Channel	16 Channel
Video Format	PAL / NISTC		
Video Format	H.264 Base Line Compression		
Video Input	BNC 4 Input / 1 Output	BNC 8 Input / 1 Output	BNC 16 Input / 1 Output
Audio Format	G.726 8Kx16bit ADPCM Mono		
Audio Input	RCA 4 Input / 1 Output	RCA 8 Input / 1 Output	RCA 16 Input / 1 Output
Alarm Type	Motion Detection, Sensor Input, Relay Output, Video Lost		
Sensor In / Out	4 CH Input / 1 CH Output		
Display Frame Rate	Each Channel PAL : 25FPS, NTSC : 30FPS		
Palyback Resolution	PAL : CIF (352 x 288), NTSC : CIF (352 x 240)		
Record Frame Rate	PAL: 100 FPS @ CIF, NTSC: 120 FPS @ CIF	PAL: 200 FPS @ CIF, NTSC: 240 FPS @ CIF	PAL: 400 FPS @ CIF, NTSC: 480 FPS @ CIF
Record Method	Power-on Auto Record, Schedule Record (Manual Record, Motion Detection, Sensor Trigger) Support Privacy Mask (Mosaic)		
HDD Interface	SATA Interface support 2000GB		
Network Protocol	TCP/IP / DHCP / DNNS / PPPoE / E-Mail		
Network Function	IE Browser Live Monitor, Configuration, Download Video, Playback, and Mobile Phone Surveillance		
USB 2.0 Interface	Mouse / Potable Mobile HDD / Flash Drive/ DVD Burner/ Firmware Upgrade		
Playback Method	Normal Play, Fast Forward, Backward, Single Step		
Network Interface	RJ45 10M / 100M Ethernet Auto Detect		
PTZ Protocol	PELCO-P, PELCO-D, Samsung, Panasonic		
Video Backup	AVI, MPEG4 or H.264 Raw		
Power Adaptor	DC 12V Adaptor / 3A		DC 12V Adaptor / 6A
Consumption	10 ~ 15W		
Temperature	10°C ~ +40°C		
Humidity	10% ~ 90%		
Dimension	(315(W) x 224 (D) x 52 (H) mm		(436(W) x 339 (D) x 5 (H) mm

© 2008 XCam. Due to continuous product development we reserve the right to change models and specifications without prior notice.

Available from:



Highest Quality – Best Performance